

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKR410524HWW-LS9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		4400 lm

保守率	良	0.86
	中	0.81
	否	0.72

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反射率 (%)	天井						壁						50						30		20		0	
θ	φ	A-A	B-B		80						70						50						30		20		0	
0°		378	378	378	70						70						50						30		10		0	
10°		378	369	374	30						30						30						30		10		0	
20°		364	350	359	10						10						10						10		0		0	
30°		330	318	329	3						3						3						3		0		0	
40°		274	273	282	1						1						1						1		0		0	
50°		195	220	220	0.6						0.6						0.6						0.6		0		0	
60°		102	162	144	0.4						0.4						0.4						0.4		0		0	
70°		48	99	60	0.3						0.3						0.3						0.3		0		0	
80°		24	37	26	0.2						0.2						0.2						0.2		0		0	
90°		1	0	1	0.1						0.1						0.1						0.1		0		0	
100°		0	0	0	0.05						0.05						0.05						0.05		0		0	
110°		0	0	0	0.03						0.03						0.03						0.03		0		0	
120°		0	0	0	0.02						0.02						0.02						0.02		0		0	
130°		0	0	0	0.01						0.01						0.01						0.01		0		0	
140°		0	0	0	0.01						0.01						0.01						0.01		0		0	
150°		0	0	0	0.01						0.01						0.01						0.01		0		0	
160°		0	0	0	0.01						0.01						0.01						0.01		0		0	
170°		0	0	0	0.01						0.01						0.01						0.01		0		0	
180°		0	0	0	0.01						0.01						0.01						0.01		0		0	

