

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKT423524HW-LD9

効 率	F 	5 %
	F 	95 %
	F 	100 %
器具光束		4950 lm

保守率	良	0.88
	中	0.86
	否	0.81

最大取付間隔		
A-A	1.3	H
B-B	1.2	H

前 面	カバー (乳白)
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反射率 (%)	天井						壁						床					
θ	φ	A-A	B-B		80						70						50					
0°		304	304	304	70	50	30	70	50	30	50	30	50	30	50	30	30	10	30	10	30	10
10°		299	298	299	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
20°		286	281	283	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
30°		263	253	258	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
40°		233	218	226	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
50°		198	176	187	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
60°		159	129	145	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
70°		121	79	103	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
80°		86	30	65	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
90°		58	2	38	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
100°		40	1	20	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
110°		13	1	1	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
120°		0	1	1	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
130°		0	1	0	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
140°		0	0	0	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
150°		0	0	0	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
160°		0	0	0	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
170°		1	0	0	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10
180°		1	1	0	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10

