

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEET-42841AT-LS9+LEEM-41203N-01

効 率	F 	4 %
	F 	96 %
	F 	100 %
器具光束		10800 lm

保守率	良	0.77
	中	0.72
	否	0.68

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

前 面	カバー (透明)
反射面	塗装 (白)



備考	LEET-42841AT-LS9+LEEM-41203N-01
----	---------------------------------

光度 (cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	302	303	303
10°	298	298	298
20°	283	283	283
30°	259	259	259
40°	227	227	227
50°	188	188	188
60°	146	146	146
70°	103	103	103
80°	66	66	66
90°	32	32	32
100°	13	13	13
110°	2	2	2
120°	1	1	1
130°	1	1	1
140°	1	1	1
150°	1	1	1
160°	1	1	1
170°	1	1	1
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数	固有照明率 (×0.01)																						
0.60	60	55	46	43	37	36	58	54	45	42	36	35	43	41	35	34	34	34	29	27			
0.80	72	65	57	54	48	46	69	64	56	53	47	45	53	51	46	44	44	43	38	36			
1.00	79	71	64	60	55	52	76	69	63	59	54	51	60	57	52	50	50	49	44	42			
1.25	87	77	73	67	63	59	83	75	71	65	62	58	67	63	59	57	57	55	50	48			
1.50	92	81	78	71	69	64	88	79	76	70	67	63	72	68	65	61	62	60	55	53			
2.00	100	87	88	79	79	72	96	85	86	78	77	71	81	75	74	70	70	68	63	60			
2.50	105	90	94	83	86	77	101	88	91	82	84	76	86	79	79	74	75	72	68	65			
3.00	108	93	99	87	91	81	104	91	96	85	89	80	90	82	84	78	79	76	72	69			
4.00	113	96	106	91	99	87	109	94	102	90	96	86	95	87	90	83	85	81	77	75			
5.00	116	98	110	94	104	90	111	96	106	92	100	89	98	89	94	86	88	84	81	78			
10.00	123	102	119	100	115	98	117	101	114	99	111	96	106	95	103	94	96	91	88	86			

