

■ 東芝照明器具配光データシート



名 称	L E D照明器具
形 名	LEER-42241AT-LS9+LEEM-41203WW-Q1

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具光 束	9400 lm

保守率	良	0.77
	中	0.72
	否	0.68

最大取付間隔		
A-A	1.3	H
B-B	1.3	H

前 面	カバー（透明）
反射面	塗装（白）

	 θ 0°
	 ϕ

備考	LEER-42241AT-LS9+LEEM-41203WW-01
----	----------------------------------

光度(cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	372	372	373
10°	370	365	368
20°	355	346	352
30°	326	314	322
40°	286	271	279
50°	231	218	226
60°	138	155	160
70°	28	86	70
80°	9	24	9
90°	0	1	0
100°	0	1	0
110°	0	1	0
120°	0	1	1
130°	0	0	1
140°	0	0	1
150°	1	0	1
160°	1	1	1
170°	1	1	1
180°	1	1	1

反射率 (%)	天井	80						70						50				30		20	0	
	壁	70		50		30		70		50		30		50		30		30		10	0	
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数	固有照明率(×0.01)																					
0.60	64	59	51	48	42	41	63	58	50	47	42	41	48	46	41	40	40	40	35	34		
0.80	77	70	64	60	55	52	75	69	62	59	54	52	60	58	53	51	52	51	46	45		
1.00	85	76	71	66	62	59	82	74	70	65	62	59	67	64	60	58	59	57	53	51		
1.25	92	82	80	73	71	67	90	81	78	72	70	66	75	71	68	65	66	64	60	58		
1.50	97	86	86	78	77	72	94	84	84	77	76	71	80	75	73	70	71	69	65	63		
2.00	106	92	96	85	88	80	102	90	93	84	86	79	89	82	83	78	80	77	73	71		
2.50	110	95	101	90	94	85	106	93	99	88	92	84	93	86	88	83	85	81	78	76		
3.00	113	97	106	93	99	89	110	96	103	92	97	88	97	89	92	86	88	85	82	80		
4.00	118	100	112	97	106	93	114	99	108	95	103	92	102	93	98	91	93	89	86	84		
5.00	120	102	115	99	110	96	116	100	111	98	107	95	105	95	101	93	96	92	89	87		
10.00	126	105	123	103	120	102	121	104	118	102	116	101	111	100	109	99	103	97	95	93		

