

■ 東芝照明器具配光データシート

名 称	東芝LED照明
形 名	LEET-42351C6T-LS9+LEEM-41203W-01

効 率	F 	7 %
	F 	93 %
	F 	100 %
	器具光	11500 lm

保守率	良	0.83
	中	0.81
	否	0.77

最大取付間隔		
A-A	1.3	H
B-B	1.2	H

前 面	カバー（乳白）
反射面	

	
	

備考	LEET-42351C6T-LS9+LEEM-41203W-01
----	----------------------------------

光度(cd/1000lm)				反射率 (%)	天井 壁 床	80						70						50				30		20	0					
$\theta \backslash \phi$	A-A	B-B	C-C			70			50			30			70			50			30			50		30	10	0		
0°	293	295	294			30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
10°	289	289	289	固有照明率(×0.01)																										
20°	276	273	274	室指数																										
30°	255	246	250	0.60	60	55	45	43	36	35	57	53	44	42	36	35	42	40	35	34	34	33	28	26						
40°	227	211	219	0.80	71	65	57	53	47	45	69	63	55	52	46	45	52	50	45	43	43	42	37	35						
50°	193	171	182	1.00	78	70	64	59	54	52	75	68	62	58	53	51	59	56	51	49	49	48	43	40						
60°	157	126	142	1.25	86	76	72	66	62	59	83	74	70	65	61	58	66	62	58	56	56	54	49	46						
70°	120	78	101	1.50	91	80	78	71	68	63	87	78	75	69	67	62	71	66	64	60	61	59	54	51						
80°	86	31	64	2.00	99	86	88	78	79	72	95	84	85	77	77	71	79	74	72	68	69	66	61	58						
90°	57	2	36	2.50	104	90	94	83	85	77	100	88	90	81	83	76	84	78	78	73	74	71	66	63						
100°	36	2	19	3.00	108	92	98	86	91	81	103	90	95	84	88	80	88	81	82	77	78	74	70	67						
110°	22	2	11	4.00	113	96	105	91	98	86	108	93	101	89	95	85	93	85	89	82	83	79	75	72						
120°	14	2	8	5.00	115	98	109	93	103	90	110	95	105	92	99	88	97	88	92	85	86	82	79	75						
130°	9	1	7	10.00	122	102	118	99	114	97	116	100	113	98	110	95	104	94	101	92	94	89	86	83						
140°	8	1	5																											
150°	6	1	4																											
160°	4	1	3																											
170°	3	1	2																											
180°	1	1	1																											

