



東芝照明器具配光データシート

名 称	LED照明器具	良	0.86		θ 
形 名	LEDD-05304W WV-RD1	保守率 中	0.81		
		否	0.72		
光源	名称				ϕ 
	形名	LED			
	光束	320 lm × 1			
前 面		効 率	F  0%	最大取付間隔	備考
			F  100%		
			F  100%		
反射面	鏡面処理		器具 光束 320 lm		
				A-A 0.3 H	
				B-B 0.3 H	

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0
0°	8282	25°	146		壁	70	50	30	70	50	30	70	50	30	70	50	30	30	10	10	0						
1°		30°	41		床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0				
2°		35°	13	照 明 率 (×0.01)																							
3°		40°	6	0.60	115	106	101	105	107	104	114	105	110	105	107	104	108	104	106	104	106	104	103	103			
4°		45°	3	0.80	121	110	117	110	115	110	120	110	116	110	114	110	115	109	113	109	112	109	109	109			
5°	6517	50°	1	1.00	119	107	115	107	112	106	118	107	114	106	111	106	111	106	109	105	108	105	105	104			
6°		55°	1	1.25	118	105	113	104	109	103	116	105	112	103	108	102	109	103	106	102	104	101	100	100			
7°		60°	0	1.50	119	105	114	104	110	102	117	104	112	103	109	102	109	102	106	101	104	100	100	99			
8°		65°	0	2.00	120	105	115	103	111	101	117	104	113	102	109	101	109	101	106	100	103	99	98	97			
9°		70°	0	2.50	122	105	117	103	113	102	118	104	114	103	111	102	110	101	107	100	103	99	98	97			
10°	3309	75°	0	3.00	123	106	119	104	115	103	120	105	116	103	113	102	111	102	108	101	104	100	99	97			
11°		80°	0	4.00	126	107	123	106	120	105	122	106	119	105	117	105	113	104	112	103	107	102	101	99			
12°		85°	0	5.00	128	108	125	107	123	107	124	107	122	107	120	106	115	105	114	105	109	103	102	101			
13°		90°	0	10.00	132	110	131	111	131	111	127	109	127	110	127	110	120	108	120	109	113	107	106	105			
14°																											
15°	1263																										
16°																											
17°																											
18°																											
19°																											
20°	389																										

