



東芝照明器具配光データシート

名 称	LED照明器具	良	0.86		θ 
形 名	LEDD-05304W-RD1	保守率	0.81		
		否	0.72		
光源	名称				ϕ 
	形名	LED			
	光束	320 lm × 1			
前 面				最大取付間隔	備考
反射面	塗装 (白)				
		効 率	F  0%	A-A 0.3 H B-B 0.3 H	
			F  100%		
			F  100%		
		器具光束	320 lm		

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0			
0°	8282	25°	146		壁	70			50			30			70			50			30			50		30		10	0	
1°		30°	41		床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
2°		35°	13	照 明 率 (×0.01)																										
3°		40°	6	室指数																										
4°		45°	3	0.60	115106110105107104114105110105107104108104106104106104103103																									
5°	6517	50°	1	0.80	121110117110115110120110116110114110115109113109112109109109																									
6°		55°	1	1.00	119107115107112106118107114106111106111106109105108105105104																									
7°		60°	0	1.25	118105113104109103116105112103108102109103106102104101100100																									
8°		65°	0	1.50	11910511410411010211710411210310910210910210610110410010099																									
9°		70°	0	2.00	120105115103111101117104113102109101109101106100103999897																									
10°	3309	75°	0	2.50	122105117103113102118104114103111102110101107100103999897																									
11°		80°	0	3.00	1231061191041151031201051161031131021111021081011041009997																									
12°		85°	0	4.00	12610712310612010512210611910511710511310411210310710210199																									
13°		90°	0	5.00	128108125107123107124107122107120106115105114105109103102101																									
14°				10.00	1321101311111131111127109127110127110120108120109113107106105																									
15°	1263																													
16°																														
17°																														
18°																														
19°																														
20°	389																													

