



東芝照明器具配光データシート

名 称	LED照明器具	良	0.86		θ 
形 名	LEDD-05305W-RD1	保守率	0.81		
		否	0.72		
光源	名称				ϕ 
	形名	LED			
	光束	520 lm x 1			
前 面				最大取付間隔	備考
反射面	塗装 (白)				
		効 率	F  0%	A-A 0.5 H B-B 0.5 H	
			F  100%		
			F  100%		
		器具光束	520 lm		

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0			
0°	4101	25°	237		壁	70			50			30			70			50			30			50		30		10	0	
1°		30°	58		床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
2°		35°	11		照 明 率 (×0.01)																									
3°		40°	4	室指数																										
4°		45°	2	0.60	1111	0210	5100	1029	9110	1021	0510	0010	2991	1010	2105	1001	0299	1041	0010	1991	1009	9998	9898							
5°	3732	50°	1	0.80	1181	0711	1310	6110	1061	1710	7112	1061	1010	6111	1061	1110	6109	1051	0710	5105	1071	0510	5104							
6°		55°	0	1.00	1171	0511	1210	4109	1031	1610	5111	1041	0810	3109	1031	0610	2105	1021	0510	2101	1011									
7°		60°	0	1.25	1171	0411	1210	2108	1011	1510	3110	1021	0610	1010	7101	1011	0410	0100	1029	9898										
8°		65°	0	1.50	1181	0411	1310	2109	1011	1610	3111	1021	0710	1010	8101	1051	0010	2998	9897											
9°		70°	0	2.00	1201	0411	1410	2110	1011	1710	3112	1021	0910	1001	0810	0105	9910	2989	9796											
10° <td>2856</td> <td>75°</td> <td>0</td> <td>2.50</td> <td>1211</td> <td>0511</td> <td>1710</td> <td>3113</td> <td>1021</td> <td>1810</td> <td>4114</td> <td>1021</td> <td>1110</td> <td>1010</td> <td>9101</td> <td>1071</td> <td>1001</td> <td>0399</td> <td>9796</td> <td colspan="4"></td>	2856	75°	0	2.50	1211	0511	1710	3113	1021	1810	4114	1021	1110	1010	9101	1071	1001	0399	9796											
11°		80°	0	3.00	1231	0511	1910	4115	1031	1910	4116	1031	1210	2101	1010	8101	1011	0499	9897											
12°		85°	0	4.00	1251	0711	2210	6119	1051	2110	6119	1051	1610	4113	1031	1110	2106	1011	0099											
13°		90°	0	5.00	1271	0711	2410	7122	1061	2310	6121	1061	1910	6114	1041	1310	4108	1021	0110											
14°				10.00	1311	0911	3011	1013	1011	2610	8126	1091	2610	9118	1071	1810	7112	1061	0510											

