


東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEET-42501-LS9+LEEM-404 03W-CG



効率	F	0 %
	F	100 %
	F	100 %
	器具光束	3050 lm

保守率	良	0.81
	中	0.77
	否	0.68

前面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	406	407	407
10°	396	396	397
20°	368	370	369
30°	326	327	326
40°	273	272	272
50°	208	210	211
60°	141	144	143
70°	73	77	75
80°	4	21	18
90°	0	1	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 ($\times 0.01$)																							
0.60	65	60	52	49	43	42	64	59	51	48	43	42	49	47	42	41	42	41	37	35					
0.80	78	71	64	60	56	53	76	69	63	60	55	53	61	58	54	52	53	52	47	46					
1.00	85	76	72	67	63	60	83	75	71	66	62	59	68	64	61	59	59	58	54	52					
1.25	93	82	80	74	71	67	90	81	79	73	70	66	75	71	68	65	67	65	60	58					
1.50	98	86	86	78	77	72	95	84	84	77	76	71	80	75	74	70	72	69	65	63					
2.00	106	92	96	85	88	80	102	90	93	84	86	79	89	83	83	78	80	77	73	71					
2.50	110	95	101	90	94	85	106	94	99	88	92	84	94	86	88	83	85	81	78	76					
3.00	113	97	106	93	99	88	110	96	103	92	97	88	97	89	92	86	89	85	82	80					
4.00	118	100	112	96	106	93	114	99	108	95	103	92	102	93	98	91	93	89	86	84					
5.00	120	102	115	99	110	96	116	100	111	98	107	95	105	95	102	93	96	92	89	87					
10.00	126	105	123	104	120	102	121	104	119	102	116	101	111	100	99	99	103	97	95	93					

