

東芝照明器具配光データシート

名 称	LED照明器具
形 名	LEER-43602-LD9+LEEM-405 23N-01

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	4700 lm

保 守 率	良	0.86
	中	0.81
	否	0.72

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	
反射面	塗装 (白)



備考

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70			50			30			70			50			30			50	30	10	0
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
					室指数	固 有 照 明 率 (×0.01)																					
0°	395	395	396	0.60	66	61	52	50	44	43	64	59	51	49	44	42	50	48	43	42	42	41	37	36			
10°	389	386	389	0.80	79	72	65	61	57	54	77	70	64	61	56	54	62	59	55	53	54	53	49	47			
20°	375	363	370	1.00	86	77	73	68	64	61	83	76	72	67	63	61	69	65	62	60	61	59	55	53			
30°	355	326	341	1.25	94	83	81	75	73	68	91	82	80	74	72	68	77	72	70	67	68	66	62	60			
40°	303	277	301	1.50	99	87	87	79	79	73	95	85	85	78	78	73	82	76	75	72	73	71	67	65			
50°	218	221	235	2.00	107	93	97	86	89	81	103	91	94	85	87	81	90	84	84	79	81	78	75	73			
60°	49	159	147	2.50	111	96	102	90	95	86	107	94	99	89	93	85	94	87	89	84	86	82	79	77			
70°	29	96	34	3.00	114	98	106	93	100	89	110	96	103	92	98	89	98	90	93	87	89	86	83	81			
80°	19	37	17	4.00	118	100	112	97	107	94	114	99	109	96	104	93	102	94	99	91	94	90	87	85			
90°	0	0	0	5.00	121	102	115	99	111	96	116	101	112	98	108	95	105	96	102	94	97	92	90	88			
100°	0	0	0	10.00	126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93			
110°	0	0	0																								
120°	0	0	0																								
130°	0	0	0																								
140°	0	0	0																								
150°	0	0	0																								
160°	0	0	0																								
170°	0	0	0																								
180°	0	0	0																								

