

東芝照明器具配光データシート

名称	LEDダウンライト
形名	LEDD87041LWLS



効 率	F ◡	0 %
	F ◒	100 %
	F ○	100 %
	器具 光束	510 lm

保 守 率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	363		
10°	355		
20°	335		
30°	305		
40°	264		
50°	215		
60°	159		
70°	95		
80°	17		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	63	58	49	47	41	39	62	57	48	46	40	39	47	45	40	39	39	38	34	32																	
0.80	76	69	62	58	53	51	74	68	61	57	52	50	59	56	51	50	50	49	44	43																	
1.00	83	75	70	65	60	57	81	73	68	64	60	57	66	62	58	56	57	55	51	49																	
1.25	91	81	78	72	69	65	88	79	76	71	68	64	73	69	66	63	64	62	58	56																	
1.50	96	85	84	76	75	70	93	83	82	75	74	69	79	74	72	68	69	67	63	61																	
2.00	105	91	94	84	86	78	101	89	92	83	84	78	87	81	81	77	78	75	71	69																	
2.50	109	94	100	88	93	83	106	93	97	87	91	83	92	85	87	81	83	80	76	74																	
3.00	113	97	105	92	98	87	109	95	102	91	96	87	96	89	91	85	87	84	80	78																	
4.00	117	100	111	96	105	92	113	98	107	95	102	92	101	93	97	90	93	88	85	83																	
5.00	120	102	115	98	110	95	116	100	111	97	107	95	104	95	101	93	96	91	89	87																	
10.00	126	105	123	104	120	102	121	104	119	102	116	101	111	100	109	99	103	97	95	93																	

