


■ 東芝照明器具配光データシート

名称	LEDダウンライト
形名	LEDD87041NWLS



効率	F	0 %
	F	100 %
	F	100 %
	器具光束	600 lm

保守率	良	0.67
	中	0.63
	否	0.56

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

$\theta \backslash \phi$	A-A	B-B	C-C
0°	361		
10°	354		
20°	334		
30°	304		
40°	264		
50°	215		
60°	159		
70°	94		
80°	16		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80					70					50					30					20					0								
	壁	70		50		30		70		50		30		50		30		30		10		0		10		0		0							
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0							
室指数	固有照明率 (×0.01)																																		
0.60	63	58	49	47	41	39	61	57	48	46	40	39	47	45	40	39	39	38	34	32															
0.80	76	69	62	58	53	50	74	67	61	57	52	50	59	56	51	50	50	49	44	43															
1.00	83	75	69	64	60	57	80	73	68	64	59	57	65	62	58	56	57	55	51	49															
1.25	91	81	78	71	69	65	88	79	76	71	68	64	73	69	66	63	64	62	58	56															
1.50	96	85	84	76	75	70	93	83	82	75	74	69	78	73	71	68	69	67	63	61															
2.00	104	91	94	84	86	78	101	89	92	83	84	78	87	81	81	76	78	75	71	69															
2.50	109	94	100	88	92	83	105	93	97	87	90	83	92	85	87	81	83	80	76	74															
3.00	113	97	104	91	98	87	109	95	101	90	95	86	96	88	91	85	87	83	80	78															
4.00	117	100	111	96	105	92	113	98	107	95	102	91	101	92	97	90	92	88	85	83															
5.00	120	101	114	98	109	95	115	100	111	97	106	94	104	95	101	92	96	91	88	86															
10.00	125	105	122	103	120	102	121	104	118	102	116	101	111	100	109	99	102	97	95	93															

