

東芝照明器具配光データシート

名 称	LEDダウンライト
形 名	LEDD87047NWLS

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		780 lm

保守率	良	0.67
	中	0.63
	否	0.56

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前 面	
反射面	



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	382		
10°	375		
20°	355		
30°	321		
40°	276		
50°	218		
60°	148		
70°	76		
80°	16		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		65	60	51	48	42	41	63	58	50	48	42	41	49	47	41	40	41	40	36	34			
0.80		77	70	64	60	55	53	75	69	63	59	54	52	61	58	53	52	52	51	47	45			
1.00		85	76	71	66	62	59	82	75	70	65	62	59	67	64	60	58	59	57	53	51			
1.25		92	82	80	73	71	66	90	81	78	72	70	66	75	71	68	65	66	64	60	58			
1.50		97	86	86	78	77	71	94	84	84	77	76	71	80	75	73	70	71	69	65	63			
2.00		106	92	96	85	88	80	102	90	93	84	86	79	89	82	83	78	80	77	73	71			
2.50		110	95	101	89	94	85	106	94	99	88	92	84	93	86	88	83	85	81	78	76			
3.00		114	97	106	93	99	88	110	96	103	92	97	88	97	89	92	86	88	85	82	80			
4.00		118	100	112	97	106	93	114	99	108	96	103	92	102	93	98	91	94	89	86	84			
5.00		121	102	115	99	110	96	116	101	112	98	107	95	105	96	102	93	97	92	89	87			
10.00		126	105	123	104	120	102	121	104	119	103	116	101	111	100	109	99	103	97	95	94			

