

■ 東芝照明器具配光データシート

名 称		L E D照明器具		保守率	良	0.67		
形 名		LEDP88114			中	0.63		
					否	0.56		
光源	名称	L E Dランプ		効 率	F 	14%	最大取付間隔	
	形名	LDA4L-G-E17 /S/40W2			F 	59%		
	光束	440 lm × 1			F 	73%		
前 面				器具 光束	325 lm		A-A	1.4 H
反射面							B-B	1.4 H
							備考	

光度(cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	155		
10°	155		
20°	152		
30°	144		
40°	131		
50°	114		
60°	95		
70°	72		
80°	48		
90°	33		
100°	31		
110°	29		
120°	25		
130°	21		
140°	16		
150°	11		
160°	6		
170°	2		
180°	1		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
	室指数	照 明 率 (×0.01)																					
	0.60	41	38	30	29	24	23	39	36	29	28	23	23	27	26	22	21	20	20	17	15		
	0.80	49	45	38	36	31	30	47	43	37	35	30	29	34	32	28	27	26	26	22	20		
	1.00	54	49	44	40	36	35	51	47	42	39	35	34	38	36	33	32	30	30	26	23		
	1.25	60	53	50	45	42	40	57	51	47	44	41	38	43	41	38	36	35	34	30	27		
	1.50	63	56	54	49	46	43	60	54	51	47	45	42	47	44	41	39	38	37	33	30		
	2.00	70	61	61	54	54	49	66	58	58	52	52	48	52	49	48	45	44	42	38	35		
	2.50	73	63	65	58	59	53	69	60	62	56	56	51	56	52	51	48	47	45	41	38		
	3.00	76	65	69	60	63	56	71	62	65	58	60	54	59	54	55	51	50	48	44	40		
	4.00	79	67	74	64	68	60	75	65	70	61	65	58	63	57	59	55	54	51	47	44		
	5.00	82	69	77	66	72	63	77	66	72	63	68	61	65	59	62	57	56	53	50	46		
	10.00	86	72	83	70	81	68	81	70	79	68	76	66	70	64	68	62	62	58	55	51		

