

東芝照明器具配光データシート

名 称		LED照明器具		保守率	良	0.67				
形 名		LEDP88114R			中	0.63				
					否	0.56				
光源	名称	LEDランプ		効 率	F 	14 %			最大取付間隔	
	形 名	LDA4L-G-E17 /S/40W2			F 	59 %				
	光束	440 lm × 1			F 	73 %				
前 面			器具 光束		325 lm	A-A				1.4 H
反射面					B-B	1.4 H			備考	

光度 (cd/1000lm)				反射率 (%)	天井				80						70						50						30				20		0	
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10		0								
					床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0					
室指数					照 明 率 (×0.01)																													
0.60					41	38	30	29	24	23	39	36	29	28	23	23	27	26	22	21	20	20	17	15										
0.80					49	45	38	36	31	30	47	43	37	35	30	29	34	32	28	27	26	26	22	20										
1.00					54	49	44	40	36	35	51	47	42	39	35	34	38	36	33	32	30	30	26	23										
1.25					60	53	50	45	42	40	57	51	47	44	41	38	43	41	38	36	35	34	30	27										
1.50					63	56	54	49	46	43	60	54	51	47	45	42	47	44	41	39	38	37	33	30										
2.00					70	61	61	54	54	49	66	58	58	52	52	48	52	49	48	45	44	42	38	35										
2.50					73	63	65	58	59	53	69	60	62	56	56	51	56	52	51	48	47	45	41	38										
3.00					76	65	69	60	63	56	71	62	65	58	60	54	59	54	55	51	50	48	44	40										
4.00					79	67	74	64	68	60	75	65	70	61	65	58	63	57	59	55	54	51	47	44										
5.00					82	69	77	66	72	63	77	66	72	63	68	61	65	59	62	57	56	53	50	46										
10.00					86	72	83	70	81	68	81	70	79	68	76	66	70	64	68	62	62	58	55	51										

