

# 東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-21003CN-LD9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	22200 lm

保守率	良	0.88
	中	0.86
	否	0.82

前面	透明
反射面	白色

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	473		
10°	471		
20°	451		
30°	390		
40°	298		
50°	187		
60°	88		
70°	42		
80°	14		
90°	7		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0	
	壁	70		50		30		70		50		30		50		30		30		10		0			
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数	固有照明率 (×0.01)																								
0.60	70	65	57	54	50	48	68	63	57	54	49	48	55	53	48	47	48	47	43	41					
0.80	83	75	70	66	62	60	81	74	69	65	62	59	67	64	61	59	60	58	54	53					
1.00	89	80	77	72	69	66	87	79	76	71	68	65	73	70	67	65	65	64	60	58					
1.25	97	86	85	78	77	72	94	84	83	77	76	72	80	76	74	71	72	70	66	64					
1.50	101	89	90	82	83	77	98	88	88	81	81	76	85	80	79	75	77	74	71	69					
2.00	108	94	99	89	92	84	105	93	97	88	90	83	92	86	87	82	84	81	78	76					
2.50	112	97	104	92	98	88	109	95	101	91	96	87	96	89	92	86	88	85	82	80					
3.00	115	99	108	95	102	91	111	97	105	94	100	90	99	92	95	89	91	87	85	83					
4.00	119	101	113	98	108	95	115	100	110	97	105	94	104	95	100	92	95	91	88	86					
5.00	121	102	116	100	112	97	117	101	113	99	109	96	106	97	103	95	98	93	91	89					
10.00	126	105	123	104	120	102	121	104	119	103	116	101	111	100	109	99	103	97	95	93					

