


東芝照明器具配光データシート

名称	東芝LED器具
形名	LEER-43002TLS9+LEEM41003N01



効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	9800 lm

保守率	良	0.81
	中	0.77
	否	0.68

前面	
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考	LEER-43002T-LS9 + LEEM-41003N-01
----	----------------------------------

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	324	325	325
10°	319	319	319
20°	305	301	303
30°	281	273	277
40°	250	235	243
50°	219	190	203
60°	178	139	165
70°	127	85	114
80°	61	32	60
90°	0	1	0
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数	固有照明率 (×0.01)																							
0.60	61	56	47	44	38	37	59	55	46	44	38	36	44	43	37	36	36	36	31	29				
0.80	73	67	59	55	49	47	71	65	58	54	49	47	55	53	48	46	47	46	41	39				
1.00	81	72	66	61	57	54	78	71	65	61	56	53	62	59	54	52	53	52	47	45				
1.25	88	79	75	68	65	61	85	77	73	68	64	60	70	66	62	59	60	58	54	52				
1.50	94	82	81	73	71	66	90	81	79	72	70	65	75	70	68	64	65	63	59	57				
2.00	102	89	91	81	82	75	98	87	88	80	80	74	84	78	77	73	74	72	67	65				
2.50	107	92	97	86	89	80	103	91	94	85	87	79	89	82	83	78	80	76	73	70				
3.00	111	95	102	89	94	84	107	93	99	88	92	83	93	86	88	82	84	80	77	75				
4.00	116	98	108	94	102	90	111	97	105	93	99	89	99	90	94	87	90	85	82	80				
5.00	118	100	112	96	107	93	114	99	109	95	104	92	102	93	98	90	93	89	86	84				
10.00	125	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	95	93	91				

