

東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LSS1MP/RP-4-64

効 率	F 	6 %
	F 	94 %
	F 	100 %
器具光束		6830 lm

保守率	良	0.88
	中	0.86
	否	0.81

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

前 面	カバー (乳白)
反射面	塗装 (白)



東芝形名: LEKTW407694SN-LS9

備考

光度 (cd/1000lm)				反射率 (%)	天井	80			70			50			30	20	0
$\theta \setminus \phi$	A-A	B-B	C-C		壁	70	50	30	70	50	30	50	30	50	30	10	0
0°	302	303	302		床	30	10	30	10	30	10	30	10	30	10	30	10
10°	297	297	298														
20°	284	281	283														
30°	262	254	259														
40°	232	219	227														
50°	196	178	188														
60°	156	132	144														
70°	116	81	99														
80°	79	30	59														
90°	49	1	30														
100°	28	1	14														
110°	17	1	8														
120°	11	1	7														
130°	9	1	6														
140°	8	1	5														
150°	6	1	4														
160°	4	1	3														
170°	2	1	2														
180°	1	1	1														
					室指数	固有照明率 (×0.01)											
					0.60	60	55	46	43	37	36	58	54	45	43	36	35
					0.80	72	65	57	54	48	46	69	64	56	53	47	45
					1.00	79	71	65	60	55	52	76	69	63	59	54	52
					1.25	87	77	73	67	63	59	83	75	71	66	62	58
					1.50	92	81	79	72	69	64	88	79	76	70	68	63
					2.00	100	87	89	79	80	73	96	85	86	78	78	72
					2.50	105	90	95	84	86	78	100	88	91	82	84	77
					3.00	108	93	99	87	92	82	104	91	96	85	89	80
					4.00	113	96	106	91	99	87	108	94	102	90	96	86
					5.00	116	98	110	94	104	90	111	96	105	92	100	89
					10.00	122	102	119	100	115	98	117	100	114	98	111	96

