

東芝照明器具配光データシート

名称	LEDシーリングライト
形名	LEDH8106B01-LC



効率	F	25%
	F	75%
	F	100%
	器具光束	4000 lm

保守率	良	0.63
	中	0.60
	否	0.56

前面	カバー (透明)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

光度 (cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	225	225	225
10°	221	221	221
20°	210	210	211
30°	190	191	192
40°	164	167	166
50°	136	140	138
60°	111	114	111
70°	88	90	86
80°	65	65	63
90°	46	46	46
100°	44	44	46
110°	42	42	45
120°	39	40	43
130°	36	37	40
140°	33	33	36
150°	29	29	31
160°	25	25	27
170°	25	25	24
180°	23	23	20

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		30		10		10		30		10		10		0					
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10				
室指数		固有照明率 (×0.01)																																			
0.60		56	52	42	40	34	33	53	49	40	39	33	32	37	36	30	29	28	27	23	20																
0.80		67	61	53	50	44	42	63	58	51	48	42	40	46	44	39	38	36	35	30	27																
1.00		74	67	60	56	50	48	70	63	57	53	48	46	52	49	44	43	41	40	34	31																
1.25		81	72	68	62	58	54	76	69	64	59	55	52	58	55	51	49	46	45	40	35																
1.50		86	76	73	66	64	59	81	72	69	64	61	57	62	58	55	53	51	49	43	39																
2.00		94	82	83	74	73	67	88	78	78	71	70	65	70	65	64	60	58	55	50	45																
2.50		99	85	88	78	80	72	93	81	84	75	76	69	74	69	69	64	62	59	54	49																
3.00		103	88	93	82	85	76	96	84	88	78	81	73	78	72	73	68	65	63	57	52																
4.00		107	91	99	86	93	81	100	87	94	83	88	78	83	76	78	72	70	67	62	56																
5.00		110	93	103	89	97	85	103	89	97	85	92	82	86	78	82	75	73	70	65	59																
10.00		117	97	113	95	109	92	109	94	106	91	102	89	93	84	91	82	80	76	72	65																

