

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB83129

保守率	良	0.63
	中	0.60
	否	0.56

--	--

光源	名称	LEDランプ
	形名	LDM20SSN/10 /10-01
	光束	1000 lm × 1

効率	F	18%
	F	63%
	F	81%
	器具光束	810 lm

最大取付間隔	
A-A	1.5 H
B-B	1.2 H

備考	

前面	
反射面	

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	150	151	151
10°	150	148	150
20°	150	140	146
30°	148	127	140
40°	143	109	130
50°	136	88	117
60°	127	64	103
70°	117	38	88
80°	105	13	74
90°	92	0	61
100°	79	0	50
110°	66	0	40
120°	52	0	31
130°	40	0	23
140°	28	0	16
150°	18	0	11
160°	10	0	5
170°	3	1	2
180°	1	1	1

反射率 (%)	天井	80						70						50						30		20		0
	壁	70	50	30	70	50	30	70	50	30	50	30	30	10	30	10	30	10	30	10	30	10	10	0
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0
室指数	照明率 (×0.01)																							
0.60	44	40	32	30	25	24	41	38	31	29	24	23	28	27	22	22	21	20	16	14				
0.80	53	48	40	38	33	31	50	45	39	36	31	30	35	33	29	28	27	26	22	19				
1.00	58	52	46	43	38	36	55	50	44	41	36	35	40	38	34	32	31	30	26	23				
1.25	64	57	53	48	44	41	60	54	50	46	42	40	45	42	39	37	36	34	30	26				
1.50	68	60	57	52	49	45	64	57	54	50	47	44	49	46	43	41	39	38	33	29				
2.00	75	65	65	58	57	52	70	62	61	56	54	50	55	51	49	47	45	43	38	35				
2.50	79	68	70	62	62	56	74	65	66	59	59	54	59	54	54	50	49	47	42	38				
3.00	82	70	74	64	67	59	77	67	69	62	63	57	62	57	57	53	51	49	45	41				
4.00	86	73	79	68	73	64	80	70	74	66	69	62	66	60	62	57	56	53	49	44				
5.00	88	75	82	71	77	67	83	72	77	68	73	65	69	63	65	60	58	55	51	47				
10.00	94	78	90	76	87	74	88	75	85	73	82	71	75	68	73	66	65	61	58	53				

