

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB83016

保守率	良	0.63
	中	0.60
	否	0.56

最大取付間隔	
A-A	1.5 H
B-B	1.2 H

光源	名称	LEDランプ
	形名	LDM10SSN/05 /5-01
	光束	500 lm × 1

効 率	F	18%
	F	66%
	F	84%
	器具 光束	420 lm

最大取付間隔		備考
A-A	1.5 H	
B-B	1.2 H	

前面	
反射面	

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	160	161	160
10°	160	158	159
20°	160	149	154
30°	157	135	146
40°	151	116	135
50°	143	94	122
60°	134	68	107
70°	122	40	92
80°	110	14	77
90°	97	0	63
100°	83	0	51
110°	68	0	40
120°	54	0	31
130°	41	0	23
140°	29	0	16
150°	19	0	11
160°	10	0	5
170°	3	0	1
180°	1	0	1

反射率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数	照明率 (×0.01)																							
0.60	46	42	34	32	26	25	43	40	32	31	25	24	29	28	23	23	22	21	17	15				
0.80	55	50	42	40	34	33	52	48	40	38	33	32	37	35	30	30	28	28	23	20				
1.00	61	55	48	45	40	38	57	52	46	43	38	36	42	40	35	34	32	32	27	24				
1.25	67	60	55	50	46	43	63	57	52	48	44	42	47	44	41	39	37	36	31	28				
1.50	71	63	60	54	51	47	67	60	57	52	49	46	51	48	45	43	41	40	35	31				
2.00	78	68	68	61	60	54	73	65	64	58	57	52	58	54	52	49	47	45	40	36				
2.50	82	71	73	64	65	59	77	68	69	62	62	57	62	57	56	53	51	49	44	40				
3.00	85	73	77	67	70	62	80	70	73	65	66	60	65	60	60	56	54	52	47	43				
4.00	90	76	82	71	76	67	84	73	78	69	72	65	69	63	65	60	58	56	51	47				
5.00	92	78	86	74	80	70	86	75	81	71	76	68	72	66	68	63	61	58	54	49				
10.00	98	82	94	80	91	77	92	79	89	77	86	74	79	71	76	69	68	64	61	56				

