

東芝照明器具配光データシート


名 称	LED照明器具
形 名	LEET77231+LEEM-G-70901L-LD9

効 率	F 	0 %
	F 	99 %
	F 	99 %
	器具光束	7130 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	1.23 H
B-B	1.23 H

前 面	カバー（プリズム）
反射面	白

θ	
	
φ	
備考	

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	404	404	404
10°	397	397	397
20°	375	375	376
30°	339	339	341
40°	287	285	287
50°	187	187	189
60°	114	115	110
70°	68	70	66
80°	33	34	45
90°	0	1	1
100°	0	0	0
110°	0	0	0
120°	0	0	0
130°	0	0	0
140°	0	0	0
150°	0	0	0
160°	0	0	0
170°	0	0	0
180°	0	0	0

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数	固有照明率 (×0.01)																							
0.60	66	60	52	50	44	43	64	59	51	49	44	42	50	48	43	42	42	42	37	36				
0.80	78	71	65	61	56	54	76	69	64	60	56	54	62	59	55	53	53	52	48	46				
1.00	85	76	72	67	63	60	82	75	71	66	62	60	68	64	61	59	60	58	54	52				
1.25	92	82	80	73	71	67	89	80	78	72	70	66	75	71	68	65	66	64	60	58				
1.50	97	85	85	78	77	71	94	84	83	77	76	71	80	75	73	70	71	69	65	63				
2.00	105	91	95	85	87	79	101	90	92	84	85	79	88	82	82	77	79	76	73	71				
2.50	109	94	100	88	93	84	105	92	97	87	91	83	92	85	87	82	84	80	77	75				
3.00	112	96	104	91	98	87	108	95	101	90	95	86	96	88	91	85	87	83	80	78				
4.00	116	99	110	95	104	92	112	98	107	94	102	91	100	92	97	89	92	88	85	83				
5.00	119	101	113	97	109	95	115	99	110	96	106	94	103	94	100	92	95	90	88	86				
10.00	124	104	121	102	118	100	120	103	117	101	114	99	109	99	107	97	101	96	94	92				

