

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ-25005N-LD2

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	25700 lm

保守率	良	0.88
	中	0.86
	否	0.82

前面	カバー (透明)
反射面	白色

最大取付間隔	
A-A	1.1 H
B-B	1.1 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	524		
10°	504		
20°	455		
30°	390		
40°	312		
50°	185		
60°	78		
70°	42		
80°	13		
90°	1		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	71	65	58	55	51	49	69	64	58	55	50	49	56	54	50	48	49	48	44	43																	
0.80	84	76	71	67	64	61	82	75	70	66	63	61	68	65	62	60	61	59	56	54																	
1.00	90	81	78	73	70	67	88	80	77	72	70	66	75	71	68	66	67	65	61	60																	
1.25	97	86	86	79	78	73	94	85	84	78	77	73	81	77	75	72	73	71	67	66																	
1.50	102	90	91	83	84	78	99	88	89	82	82	77	86	80	80	76	78	75	72	70																	
2.00	109	95	100	89	93	85	106	93	98	88	91	84	93	87	88	83	85	82	79	77																	
2.50	113	97	105	93	99	89	109	96	102	92	96	88	97	90	93	87	89	85	83	81																	
3.00	116	99	109	95	103	92	112	98	106	94	101	91	100	92	96	90	92	88	85	84																	
4.00	119	102	114	98	109	96	115	100	110	97	106	95	104	95	101	93	96	92	89	87																	
5.00	122	103	117	100	113	98	117	102	113	99	109	97	107	97	104	95	98	94	91	90																	
10.00	126	105	123	104	121	103	122	104	119	103	117	102	112	101	110	100	104	98	96	94																	

