

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ34005DNLD9+LEDX20071G

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	30800 lm

保守率	良	0.88
	中	0.86
	否	0.82

前面	ガード
反射面	白色

最大取付間隔	
A-A	1.1 H
B-B	1.1 H

備考	LEDJ-34005DN-LD9+LEDX-20071G

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	592		
10°	570		
20°	509		
30°	424		
40°	294		
50°	168		
60°	90		
70°	20		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	74	68	61	58	54	52	72	67	61	58	54	52	59	57	53	52	52	51	48	46																	
0.80	86	78	75	70	67	64	84	77	74	70	67	64	72	68	66	64	64	63	60	58																	
1.00	93	83	81	76	74	70	90	82	80	75	73	70	78	74	72	69	70	68	65	63																	
1.25	99	88	89	81	81	76	97	87	87	81	80	76	84	79	78	75	76	74	71	69																	
1.50	104	91	94	85	87	80	101	90	92	84	85	80	88	83	83	79	81	78	75	73																	
2.00	111	96	102	91	96	87	107	95	100	90	94	87	95	89	91	85	88	84	82	80																	
2.50	114	99	107	94	101	91	111	97	104	93	99	90	99	92	95	89	91	88	85	83																	
3.00	117	100	110	97	105	94	113	99	107	96	103	93	102	94	98	91	94	90	88	86																	
4.00	120	102	115	100	111	97	116	101	112	99	108	96	106	97	103	95	98	93	91	89																	
5.00	122	104	118	101	114	99	118	102	114	100	111	98	108	98	105	97	100	95	93	91																	
10.00	127	106	124	105	122	104	122	105	120	104	118	103	112	102	111	101	105	99	97	95																	

