

東芝照明器具配光データシート

名称	LED高天井用照明器具
形名	LEDJ43006NLD9+LEDX20071G

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具光束	38000 lm

保守率	良	0.88
	中	0.86
	否	0.82

前面	ガード
反射面	アルミ蒸着処理

最大取付間隔	
A-A	0.7 H
B-B	0.7 H

備考	LEDJ-43006N-LD9+LEDX-20071G

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	1167		
10°	1022		
20°	732		
30°	416		
40°	272		
50°	96		
60°	3		
70°	1		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	86	79	76	72	70	68	85	78	75	72	70	68	74	71	69	67	68	67	65	63																	
0.80	98	89	89	83	83	79	96	88	88	83	82	79	86	82	81	79	80	78	76	75																	
1.00	102	92	93	86	87	83	100	91	92	86	86	82	90	85	85	82	83	81	79	78																	
1.25	107	95	98	90	92	87	104	94	97	90	91	86	94	88	89	85	87	85	82	81																	
1.50	110	97	102	93	96	90	107	96	100	92	95	89	97	91	93	88	90	87	85	84																	
2.00	115	100	108	97	103	94	112	99	106	96	101	93	102	94	98	92	95	91	89	88																	
2.50	118	102	112	99	107	96	114	101	109	98	105	96	104	96	101	94	97	93	91	90																	
3.00	120	103	115	100	110	98	116	102	112	99	108	97	106	98	103	96	99	95	93	91																	
4.00	123	104	118	102	115	101	119	103	115	101	112	100	109	100	106	98	102	97	95	94																	
5.00	124	105	121	104	117	102	120	104	117	103	114	101	111	101	108	100	103	98	97	95																	
10.00	128	107	126	106	124	105	123	106	122	105	120	104	114	103	113	103	107	101	99	98																	

