

東芝照明器具配光データシート

名称	LED防爆器具
形名	LEDQ-35821SEC-LS9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	3500 lm

保 守 率	良	0.96
	中	0.93
	否	0.89

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備 考	
--------	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	338		
10°	332		
20°	314		
30°	287		
40°	250		
50°	204		
60°	156		
70°	107		
80°	44		
90°	1		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	
室指数	固有照明率 (×0.01)																							
0.60	62	57	48	45	39	38	60	56	47	45	39	37	45	44	38	37	37	36	32	30				
0.80	74	67	60	56	50	48	72	66	59	55	50	48	57	54	49	47	48	47	42	40				
1.00	81	73	67	62	58	55	79	72	66	62	57	54	63	60	56	54	54	53	48	46				
1.25	89	79	76	69	66	62	86	78	74	68	65	62	71	67	63	61	61	60	55	53				
1.50	94	83	82	74	72	67	91	81	80	73	71	67	76	71	69	65	67	64	60	58				
2.00	103	89	92	82	83	76	99	88	89	81	81	75	85	79	78	74	75	73	68	66				
2.50	108	93	98	86	90	81	104	91	95	85	88	80	90	83	84	79	81	77	74	71				
3.00	111	95	103	90	95	85	107	94	100	89	93	84	94	86	89	83	85	81	78	75				
4.00	116	99	109	94	103	90	112	97	106	93	100	89	99	91	95	88	90	86	83	81				
5.00	119	100	113	97	108	94	114	99	109	96	104	93	103	93	99	91	94	89	86	84				
10.00	125	104	122	103	119	101	120	103	117	101	115	100	110	99	108	98	101	96	94	92				

