

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB88948 (K)

保守率	良	0.63
	中	0.60
	否	0.56

最大取付間隔	
A-A	1.5 H
B-B	1.5 H

光源	名称	LEDランプ
	形名	LDA4N-H-E17 /S/40W2
	光束	440 lm × 1

効 率	F ◡	24 %
	F ◣	53 %
	F ○	77 %
	器具 光束	340 lm

備考	
A-A	1.5 H
B-B	1.5 H

前面	
反射面	

θ \ φ	A-A	B-B	C-C
0°	108	108	108
10°	110	110	111
20°	110	110	113
30°	107	107	111
40°	100	100	106
50°	92	92	99
60°	81	81	89
70°	70	70	79
80°	57	56	67
90°	46	45	57
100°	45	44	55
110°	42	41	52
120°	37	37	47
130°	32	32	40
140°	26	26	33
150°	19	19	25
160°	13	13	16
170°	6	6	7
180°	1	1	1

反射率 (%)	天井	80						70						50						30						20						0																
	壁	70		50		30		70		50		30		50		30		30		30		10		10		30		10		10																		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10																			
室指数	照明率 (×0.01)																																															
0.60	40	37	29	28	23	22	38	35	28	26	21	21	25	24	19	19	17	17	13	11																												
0.80	48	44	37	35	30	28	45	41	35	33	28	27	31	29	25	24	22	22	18	15																												
1.00	54	48	42	39	35	33	50	45	40	37	33	31	35	33	29	28	26	25	21	18																												
1.25	59	53	48	44	40	38	55	50	45	42	38	36	40	37	34	33	30	29	25	21																												
1.50	63	56	53	48	45	41	59	52	49	45	42	40	43	40	38	36	33	32	27	23																												
2.00	69	60	60	53	52	48	64	57	56	51	49	46	49	45	44	41	38	37	32	28																												
2.50	73	63	64	57	57	52	68	60	60	54	54	49	52	48	48	45	42	40	35	31																												
3.00	76	65	68	60	62	55	70	62	64	57	58	52	55	51	51	47	44	43	38	33																												
4.00	80	68	73	63	67	59	74	64	68	60	63	56	59	54	55	51	48	46	41	36																												
5.00	82	69	76	66	71	62	76	66	71	62	67	59	62	56	58	54	51	48	44	38																												
10.00	87	73	84	71	81	69	81	70	78	67	75	65	68	61	65	59	57	53	50	44																												

