

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDB88948 (S)

保守率	良	0.63
	中	0.60
	否	0.56

最大取付間隔	
A-A	1.5 H
B-B	1.5 H

光源	名称	LEDランプ
	形名	LDA4N-H-E17 /S/40W2
	光束	440 lm × 1

効率	F	25%
	F	53%
	F	78%
	器具光束	340 lm

備考	
----	--

前面	
反射面	

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	104	104	104
10°	106	106	107
20°	107	107	110
30°	104	104	109
40°	99	98	105
50°	91	91	98
60°	81	81	90
70°	70	70	80
80°	58	57	69
90°	46	46	58
100°	45	45	57
110°	42	43	53
120°	38	38	48
130°	33	33	42
140°	27	27	34
150°	20	20	26
160°	13	13	17
170°	7	7	8
180°	1	1	1

反射率 (%)	天井			80			70			50			30		20		0			
	壁	70	50	30	70	50	30	50	30	30	10	30	10	30	10	10	0			
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0	0			
室指数	照明率 (×0.01)																			
0.60	40	37	29	28	22	22	38	35	28	26	21	21	24	23	19	19	17	17	13	10
0.80	49	44	37	35	29	28	45	41	35	33	28	27	31	29	25	24	22	22	18	15
1.00	54	48	42	39	34	33	50	45	40	37	33	31	35	33	29	28	26	25	21	17
1.25	59	53	48	44	40	38	55	50	45	42	38	36	40	37	34	32	30	29	24	21
1.50	63	56	53	48	45	41	59	52	49	45	42	39	43	40	37	36	33	32	27	23
2.00	70	60	60	54	52	48	64	57	56	51	49	46	49	45	44	41	38	37	32	27
2.50	73	63	65	57	57	52	68	60	60	54	54	49	52	48	48	44	42	40	35	30
3.00	76	65	68	60	62	55	71	62	64	57	58	52	55	51	51	47	44	42	38	33
4.00	80	68	73	63	68	59	74	64	68	60	63	57	59	54	55	51	48	46	41	36
5.00	82	70	77	66	72	62	76	66	71	62	67	59	62	56	58	54	51	48	44	38
10.00	88	73	84	71	81	69	81	70	78	68	76	66	68	61	65	59	57	53	49	44

