

# 東芝照明器具配光データシート

名称	LED照明器具
形名	LEDG88942 (K)

保守率	良	0.63
	中	0.60
	否	0.56

--	--

光源	名称	LEDランプ
	形名	LDA6N-H-E17 /S/60W2
	光束	760 lm × 1

効 率	F ◡	3 %
	F ◣	42 %
	F ○	45 %
	器具 光束	340 lm

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

備考	

前面	
反射面	

θ \ φ	A-A B-B C-C		
	0°	190	
10°	186		
20°	182		
30°	161		
40°	121		
50°	80		
60°	46		
70°	20		
80°	7		
90°	5		
100°	6		
110°	6		
120°	5		
130°	4		
140°	3		
150°	2		
160°	1		
170°	1		
180°	1		

反射率 (%)	天井																			
	80				70				50				30	20	0					
	70	50	30	10	70	50	30	10	50	30	10	10	30	10	0					
室指数	照 明 率 (×0.01)																			
0.60	29	26	22	21	19	18	28	26	22	21	18	18	21	20	18	18	17	17	15	14
0.80	34	30	28	26	24	23	32	30	27	25	23	22	26	25	23	22	22	21	19	18
1.00	38	34	32	30	28	27	37	33	31	29	27	26	30	28	27	26	26	25	23	22
1.25	41	36	36	33	32	30	40	36	35	32	31	29	33	31	30	29	29	28	26	25
1.50	43	38	38	35	35	32	42	37	37	34	34	32	35	33	32	31	31	30	28	27
2.00	47	41	42	38	39	36	45	40	41	37	38	35	39	36	36	34	34	33	31	30
2.50	49	42	45	40	42	38	47	41	43	39	41	37	41	38	39	36	37	35	33	32
3.00	50	43	47	41	44	39	48	42	45	40	43	39	42	39	40	37	38	36	35	34
4.00	52	44	49	43	47	41	50	43	47	42	45	40	44	40	43	39	40	38	37	35
5.00	53	45	51	44	49	42	51	44	49	43	47	42	45	41	44	40	41	39	38	37
10.00	56	46	54	46	53	45	53	46	52	45	51	44	48	43	47	43	44	41	40	39

