

東芝照明器具配光データシート

名 称	LED照明器具	良	0.63		
形 名	LEDG88942 (S)	保守率	中	0.60	
			否	0.56	
光源	名称 LEDランプ				
	形名 LDA6N-H-E17 / S/60W2	効 率	F 	3 %	
	光束 760 lm × 1		F 	47 %	
前 面			F 	50 %	
反射面			器具光束	380 lm	
					最大取付間隔
					A-A 1.3 H
					B-B 1.3 H
					備考

光度 (cd/1000lm)				天井	80				70				50				30	20	0
θ \ φ	A-A	B-B	C-C	壁	70	50	30		70	50	30		50	30			30	10	0
0°	198			床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
10°	196			室指数	照 明 率 (×0.01)														
20°	193			0.60	31	29	24	23	20	20	30	28	24	23	20	19	23	22	19
30°	173			0.80	37	33	30	28	26	25	36	33	29	28	25	24	28	27	24
40°	134			1.00	42	37	35	32	30	29	40	36	34	32	30	29	32	31	29
50°	91			1.25	45	40	39	36	35	32	43	39	38	35	34	32	36	34	33
60°	54			1.50	48	42	42	38	38	35	46	41	41	38	37	35	39	36	35
70°	24			2.00	52	45	47	42	43	39	50	44	45	41	42	38	43	40	40
80°	9			2.50	54	46	49	44	46	41	52	45	48	43	45	41	45	41	42
90°	6			3.00	55	48	52	45	48	43	53	47	50	44	47	42	47	43	44
100°	6			4.00	57	49	54	47	52	45	55	48	52	46	50	45	49	45	47
110°	6			5.00	59	50	56	48	54	47	56	49	54	47	52	46	50	46	48
120°	6			10.00	61	51	60	50	58	50	59	50	57	50	56	49	53	48	52
130°	4																		
140°	3																		
150°	2																		
160°	1																		
170°	1																		
180°	1																		

