


東芝照明器具配光データシート

名 称	東芝LED器具
形 名	LEKTW407104SNM-LS9

効 率	F 	6 %
	F 	94 %
	F 	100 %
	器具 光束	9380 lm

保 守 率	良	0.88
	中	0.86
	否	0.81



前 面	カバー (乳白)
反射面	塗装 (白)

最大取付間隔	
A-A	1.3 H
B-B	1.2 H

備考

光度 (cd/1000lm)				反 射 率 (%)	天井	80						70						50						30		20	0	
$\theta \backslash \phi$	A-A	B-B	C-C		壁	70		50		30		70		50		30		50		30		30		10	0			
					固有照明率 (×0.01)																							
0°	302	303	302	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
10°	297	297	298	室指数																								
20°	284	281	283	0.60	60	55	46	43	37	36	58	54	45	43	36	35	43	41	35	35	34	34	29	27				
30°	262	254	259	0.80	72	65	57	54	48	46	69	64	56	53	47	45	53	51	46	44	44	43	38	36				
40°	232	219	227	1.00	79	71	65	60	55	52	76	69	63	59	54	52	60	57	52	50	50	49	44	42				
50°	196	178	188	1.25	87	77	73	67	63	59	83	75	71	66	62	58	67	63	59	57	57	55	50	48				
60°	156	132	144	1.50	92	81	79	72	69	64	88	79	76	70	68	63	72	67	65	62	62	60	55	52				
70°	116	81	99	2.00	100	87	89	79	80	73	96	85	86	78	78	72	80	75	74	70	70	67	63	60				
80°	79	30	59	2.50	105	90	95	84	86	78	100	88	91	82	84	77	85	79	79	74	75	72	68	65				
90°	49	1	30	3.00	108	93	99	87	92	82	104	91	96	85	89	80	89	82	84	78	79	76	72	69				
100°	28	1	14	4.00	113	96	106	91	99	87	108	94	102	90	96	86	94	86	90	83	84	80	77	74				
110°	17	1	8	5.00	116	98	110	94	104	90	111	96	105	92	100	89	98	89	94	86	88	83	80	77				
120°	11	1	7	10.00	122	102	119	100	115	98	117	100	114	98	111	96	105	95	103	93	95	90	87	84				
130°	9	1	6																									
140°	8	1	5																									
150°	6	1	4																									
160°	4	1	3																									
170°	2	1	2																									
180°	1	1	1																									

