

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEKD25013MN-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		2500 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	0.7 H
B-B	0.7 H

前 面	下面開放
反射面	白色



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	1391		
10°	1217		
20°	857		
30°	439		
40°	159		
50°	48		
60°	24		
70°	0		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		固有照明率 (×0.01)																						
0.60		91	84	82	78	77	74	90	83	82	78	76	74	80	77	76	74	75	74	71	70			
0.80		102	93	94	88	89	85	100	92	93	88	88	85	91	87	87	84	86	84	82	81			
1.00		105	95	97	90	92	87	103	94	96	90	91	87	94	89	89	86	88	86	84	83			
1.25		109	97	101	93	96	90	107	96	100	92	94	89	97	91	92	89	90	88	86	85			
1.50		112	99	104	95	99	92	109	98	103	94	98	92	99	93	95	91	93	90	88	87			
2.00		116	101	110	98	105	95	113	100	107	97	103	95	103	96	99	94	96	93	91	90			
2.50		119	102	113	100	108	98	115	101	110	99	106	97	105	97	102	96	98	94	93	91			
3.00		121	103	115	101	111	99	117	102	112	100	109	98	107	99	104	97	100	96	94	93			
4.00		123	105	119	103	116	102	119	104	116	102	113	101	110	100	107	99	103	98	96	95			
5.00		125	106	122	104	118	103	121	105	118	103	115	102	111	101	109	101	104	99	98	96			
10.00		129	107	127	107	125	106	124	106	123	106	121	105	115	104	114	104	108	102	101	99			

