


東芝照明器具配光データシート

| | |
|----|----------------|
| 名称 | 東芝LED照明器具 |
| 形名 | CSKDD010102L05 |



| | | |
|--------|----------|--------|
| 効 率 | F ◡ | 1 % |
| | F ◡ | 99 % |
| | F ○ | 100 % |
| | 器具 光束 | 900 lm |

| | | |
|---------|---|------|
| 保守 率 | 良 | 0.81 |
| | 中 | 0.77 |
| | 否 | 0.68 |

| | |
|-----|------|
| 前面 | 下面開放 |
| 反射面 | 白色 |

| | |
|--------|-------|
| 最大取付間隔 | |
| A-A | 1.3 H |
| B-B | 1.3 H |

備考

| 光度 (cd/1000lm) | | | |
|----------------|-----|-----|-----|
| θ \ φ | A-A | B-B | C-C |
| 0° | 379 | | |
| 10° | 368 | | |
| 20° | 350 | | |
| 30° | 323 | | |
| 40° | 272 | | |
| 50° | 201 | | |
| 60° | 130 | | |
| 70° | 73 | | |
| 80° | 33 | | |
| 90° | 11 | | |
| 100° | 5 | | |
| 110° | 0 | | |
| 120° | 0 | | |
| 130° | 0 | | |
| 140° | 0 | | |
| 150° | 0 | | |
| 160° | 0 | | |
| 170° | 0 | | |
| 180° | 0 | | |

| 反射 率 (%) | 天井 | 80 | | | | | | 70 | | | | | | 50 | | | | | | 30 | | | | | | 20 | | | | | | 0 | | | | | | | | | | | | | | | | |
|----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|--|--|--|--|--|--|--|--|--|--|--|--|--|
| | 壁 | 70 | | 50 | | 30 | | 70 | | 50 | | 30 | | 50 | | 30 | | 30 | | 10 | | 0 | | 30 | | 10 | | 0 | | 30 | | 10 | | 0 | | | | | | | | | | | | | | |
| | 床 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | 30 | 10 | | | | | | | | | | | | | |
| 室指数 | 固有照明率 (×0.01) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.60 | 64 | 59 | 51 | 48 | 42 | 41 | 63 | 58 | 50 | 47 | 42 | 41 | 48 | 46 | 41 | 40 | 40 | 40 | 35 | 34 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.80 | 77 | 70 | 63 | 59 | 54 | 52 | 75 | 68 | 62 | 59 | 54 | 52 | 60 | 57 | 53 | 51 | 51 | 50 | 46 | 44 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.00 | 84 | 75 | 71 | 65 | 62 | 58 | 81 | 74 | 69 | 65 | 61 | 58 | 66 | 63 | 59 | 57 | 58 | 56 | 52 | 50 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.25 | 92 | 81 | 79 | 72 | 70 | 65 | 89 | 80 | 77 | 71 | 69 | 65 | 74 | 69 | 67 | 64 | 65 | 63 | 58 | 56 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1.50 | 96 | 85 | 85 | 77 | 76 | 70 | 93 | 83 | 82 | 76 | 74 | 70 | 79 | 74 | 72 | 69 | 70 | 67 | 63 | 61 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.00 | 104 | 91 | 94 | 84 | 86 | 79 | 101 | 89 | 92 | 83 | 84 | 78 | 87 | 81 | 81 | 76 | 78 | 75 | 71 | 69 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2.50 | 109 | 94 | 100 | 88 | 92 | 83 | 105 | 92 | 97 | 87 | 90 | 82 | 92 | 85 | 86 | 81 | 83 | 79 | 76 | 74 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3.00 | 112 | 96 | 104 | 91 | 97 | 87 | 108 | 95 | 101 | 90 | 95 | 86 | 95 | 88 | 90 | 84 | 86 | 83 | 79 | 77 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4.00 | 117 | 99 | 110 | 95 | 104 | 92 | 112 | 98 | 106 | 94 | 101 | 91 | 100 | 92 | 96 | 89 | 91 | 87 | 84 | 82 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5.00 | 119 | 101 | 114 | 97 | 108 | 94 | 115 | 99 | 110 | 96 | 105 | 93 | 103 | 94 | 99 | 91 | 94 | 89 | 87 | 85 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10.00 | 125 | 104 | 121 | 102 | 118 | 101 | 120 | 103 | 117 | 101 | 114 | 100 | 109 | 99 | 107 | 97 | 101 | 95 | 93 | 91 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

