

東芝照明器具配光データシート


名 称	LED高天井用照明器具
形 名	LEDJ21902JN-LS9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束	22700 lm	

保守率	良	0.88
	中	0.86
	否	0.81

最大取付間隔	
A-A	1.1 H
B-B	1.1 H

前 面	カバー（透明）
反射面	白色



備考	暫定配光図
----	-------

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	527		
10°	505		
20°	469		
30°	391		
40°	326		
50°	199		
60°	71		
70°	31		
80°	6		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		固有照明率 (×0.01)																						
0.60		72	66	59	56	51	50	70	65	58	55	51	50	57	55	50	49	50	49	45	43			
0.80		85	77	72	68	65	62	82	76	71	67	64	62	69	66	63	61	62	60	57	55			
1.00		91	82	79	74	72	68	89	81	78	73	71	68	76	72	69	67	68	66	62	61			
1.25		98	87	87	80	79	74	95	86	86	79	78	74	82	78	76	73	74	72	69	67			
1.50		103	90	92	84	85	79	100	89	91	83	84	78	87	82	81	77	79	76	73	71			
2.00		110	96	101	90	94	86	106	94	99	89	93	85	94	88	89	84	86	83	80	78			
2.50		114	98	106	94	100	90	110	97	103	93	98	89	98	91	94	88	90	87	84	82			
3.00		116	100	110	96	104	93	113	99	107	95	102	92	101	93	97	91	93	89	87	85			
4.00		120	102	115	99	110	97	116	101	111	98	107	96	105	96	102	94	97	93	90	89			
5.00		122	103	118	101	113	99	118	102	114	100	110	98	107	98	105	96	99	94	92	91			
10.00		127	106	124	104	121	103	122	105	120	103	118	102	112	101	110	100	104	98	97	95			

