

東芝照明器具配光データシート


名 称	東芝LED照明器具
形 名	LEDD-18005M-LS9 + LEEU-1005N-03

効 率	F 	0 %
	F 	100 %
	F 	100 %
	器具 光束	890 lm

保 守 率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	1.0 H
B-B	1.0 H

前 面	下面開放
反射面	白色



備考	LEDD-18005M-LS9+LEEU-1005N-03
----	-------------------------------

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	667		
10°	638		
20°	520		
30°	385		
40°	274		
50°	169		
60°	93		
70°	26		
80°	6		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固 有 照 明 率 (×0.01)																						
0.60		74	68	62	59	55	53	72	67	61	58	54	53	60	57	54	52	53	52	48	47			
0.80		86	78	75	70	67	65	84	77	74	70	67	64	72	68	66	64	65	63	60	58			
1.00		93	83	81	75	74	70	90	82	80	75	73	69	77	73	71	69	70	68	65	63			
1.25		99	88	88	81	81	76	96	87	87	80	80	75	84	79	78	74	76	74	70	69			
1.50		103	91	93	85	86	80	100	90	91	84	85	79	88	82	82	78	80	77	74	73			
2.00		110	96	102	91	95	87	107	94	99	90	93	86	95	88	90	85	87	84	81	79			
2.50		114	98	106	94	100	90	110	97	104	93	98	90	99	91	94	88	91	87	84	83			
3.00		117	100	110	96	104	93	113	99	107	95	102	92	101	93	98	91	94	89	87	85			
4.00		120	102	115	99	110	97	116	101	111	98	107	96	105	96	102	94	97	93	91	89			
5.00		122	103	118	101	114	99	118	102	114	100	111	98	108	98	105	96	100	95	93	91			
10.00		127	106	124	105	122	104	122	105	120	104	118	103	112	101	111	101	104	99	97	95			

