

東芝照明器具配光データシート


名 称	東芝LED照明器具
形 名	LEKD203025NV-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		2200 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	1.0 H
B-B	1.0 H

前 面	下面開放
反射面	銀色鏡面仕上げ



備考	LEKD203025NV-LD9
----	------------------

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	656		
10°	620		
20°	510		
30°	401		
40°	285		
50°	193		
60°	91		
70°	6		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70		50		30		70		50		30		50		30		30		10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0		
室指数		固有照明率 (×0.01)																					
0.60		74	68	62	59	55	53	72	67	61	58	54	53	60	57	54	52	53	52	48	47		
0.80		87	79	75	71	68	65	85	78	74	70	67	65	72	69	66	64	65	64	60	59		
1.00		93	84	82	76	74	71	91	82	81	75	74	70	78	74	72	69	71	69	65	64		
1.25		100	89	89	82	82	77	97	87	88	81	81	76	85	80	79	75	77	75	71	70		
1.50		104	92	94	86	87	81	101	90	92	85	86	80	89	83	83	79	81	79	75	74		
2.00		111	96	103	92	96	88	108	95	100	91	94	87	96	89	91	86	88	85	82	80		
2.50		114	99	107	95	101	91	111	98	105	94	99	91	100	92	95	89	92	88	86	84		
3.00		117	100	111	97	105	94	113	99	108	96	103	93	102	94	99	92	95	90	88	86		
4.00		121	103	115	100	111	98	117	101	112	99	108	97	106	97	103	95	98	94	92	90		
5.00		123	104	118	102	114	100	118	102	115	101	111	99	108	99	106	97	100	95	93	92		
10.00		127	106	124	105	122	104	122	105	120	104	118	103	113	102	111	101	105	99	97	96		

