

東芝照明器具配光データシート

名称	東芝LED照明器具
形名	LEKD252923WW-LS9



効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	2100 lm

保 守 率	良	0.77
	中	0.72
	否	0.68

前面	カバー (透明)
反射面	塗装 (白)

最大取付間隔	
A-A	0.8 H
B-B	0.8 H

備考	LEKD252923WW-LS9
----	------------------

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	893		
10°	786		
20°	579		
30°	448		
40°	289		
50°	129		
60°	35		
70°	21		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30						20						0					
	壁	70		50		30		70		50		30		50		30		30		10		30		10		10		0									
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10								
室指数	固有照明率 (×0.01)																																				
0.60	79	73	68	65	62	60	78	72	68	65	61	60	66	64	61	59	60	59	56	54																	
0.80	92	83	81	76	75	71	90	82	80	76	74	71	78	75	73	71	72	70	67	66																	
1.00	97	87	87	81	80	76	95	86	86	80	79	76	83	79	78	75	76	74	71	70																	
1.25	103	91	93	85	86	81	100	90	92	85	85	81	89	83	83	80	81	79	76	75																	
1.50	107	94	98	89	91	85	104	93	96	88	90	84	92	87	87	83	85	82	80	78																	
2.00	113	98	105	94	99	90	109	97	103	93	97	90	98	91	94	89	91	87	85	84																	
2.50	116	100	109	96	104	93	112	99	106	96	102	93	101	94	98	91	94	90	88	86																	
3.00	118	101	112	98	107	96	115	100	109	97	105	95	104	96	100	94	96	92	90	88																	
4.00	121	103	117	101	112	99	117	102	113	100	110	98	107	98	104	96	100	95	93	91																	
5.00	123	104	119	102	116	101	119	103	116	101	112	100	109	99	107	98	101	96	95	93																	
10.00	127	106	125	105	123	104	123	105	121	104	119	103	113	102	112	101	105	100	98	96																	

