

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEKD2033025NV-LS9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		1910 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	0.5 H
B-B	0.5 H

前 面	下面開放
反射面	銀色鏡面仕上げ



備考	LEKD2033025NV-LS9
----	-------------------

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	1893		
10°	1399		
20°	683		
30°	403		
40°	230		
50°	45		
60°	12		
70°	1		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		91	84	82	78	77	74	90	83	81	78	76	74	80	77	76	74	75	73	71	70			
0.80		102	92	94	88	88	85	100	92	93	87	88	84	91	87	87	84	85	84	82	81			
1.00		105	94	97	90	92	87	103	94	96	90	91	87	93	89	89	86	88	85	83	82			
1.25		109	97	101	93	95	90	107	96	99	92	94	89	97	91	92	88	90	88	86	84			
1.50		112	98	104	95	99	92	109	98	103	94	98	91	99	93	95	91	93	90	88	87			
2.00		116	101	110	98	104	95	113	100	107	97	103	95	103	96	99	94	96	93	91	89			
2.50		119	102	113	100	108	97	115	101	110	99	106	97	105	97	102	96	98	94	93	91			
3.00		121	103	115	101	111	99	117	102	112	100	109	98	107	98	104	97	100	96	94	92			
4.00		123	105	119	103	115	101	119	104	116	102	113	101	110	100	107	99	102	98	96	95			
5.00		125	106	121	104	118	103	121	104	118	103	115	102	111	101	109	100	104	99	97	96			
10.00		128	107	127	107	125	106	124	106	123	106	121	105	115	104	114	103	108	102	101	99			

