



■ 東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEKG102421N-LD9

効 率	F 	0 %
	F 	1 0 0 %
	F 	1 0 0 %
	器具 光束	1 0 7 0 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	0.9 H
B-B	0.9 H

備考	LEKG102421N-LD9
----	-----------------

光度 (cd/1000lm)			
$\theta \backslash \phi$	A-A	B-B	C-C
0°	666		
10°	634		
20°	511		
30°	374		
40°	273		
50°	163		
60°	94		
70°	42		
80°	5		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0			
室指数		固有照明率 (×0.01)																						
0.60		73	68	61	58	54	52	72	67	61	58	54	52	59	57	53	52	52	51	48	46			
0.80		86	78	74	69	66	64	84	77	73	69	66	63	71	68	65	63	64	62	59	57			
1.00		92	83	80	75	73	69	90	81	79	74	72	69	77	73	70	68	69	67	64	62			
1.25		98	87	88	80	80	75	96	86	86	80	79	74	83	78	77	74	75	73	69	68			
1.50		103	91	93	84	85	79	100	89	91	83	84	79	87	82	81	78	79	77	73	72			
2.00		110	95	101	90	94	86	106	94	99	89	92	85	94	88	89	84	86	83	80	78			
2.50		113	98	106	93	99	90	110	97	103	92	97	89	98	91	94	88	90	86	84	82			
3.00		116	100	109	96	104	93	112	98	106	95	101	92	101	93	97	90	93	89	86	85			
4.00		120	102	114	99	110	96	116	101	111	98	107	96	105	96	102	94	97	92	90	88			
5.00		122	103	117	101	113	99	118	102	114	100	110	98	107	98	104	96	99	94	92	91			
10.00		127	106	124	105	122	104	122	105	120	104	118	103	112	101	111	101	104	99	97	95			

