

東芝照明器具配光データシート


名 称	東芝LED照明器具
形 名	LEDD-186405M-LS9 + LEEU-2505L-03

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		1780 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	0.7 H
B-B	0.7 H

前 面	下面開放
反射面	白色



備考	LEDD-186405M-LS9+LEEU-2505L-03
----	--------------------------------

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	964		
10°	845		
20°	591		
30°	448		
40°	295		
50°	105		
60°	28		
70°	17		
80°	8		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		81	74	70	66	63	61	79	73	69	66	63	61	68	65	62	61	62	60	57	56			
0.80		93	84	83	78	76	73	91	83	82	77	75	73	80	76	74	72	73	72	69	68			
1.00		98	88	88	82	81	77	96	87	87	81	80	77	84	80	79	76	78	76	73	71			
1.25		103	92	94	86	87	82	101	91	92	85	86	81	89	84	84	81	82	80	77	76			
1.50		107	94	98	89	92	85	104	93	96	89	91	85	93	87	88	84	86	83	80	79			
2.00		113	98	105	94	99	91	110	97	103	93	98	90	99	92	94	89	91	88	85	84			
2.50		116	100	109	97	104	94	112	99	107	96	102	93	102	94	98	92	94	90	88	87			
3.00		118	101	112	98	107	96	115	100	109	97	105	95	104	96	100	94	96	92	90	89			
4.00		121	103	117	101	112	99	117	102	113	100	109	98	107	98	104	96	99	95	93	91			
5.00		123	104	119	102	115	100	119	103	115	101	112	100	109	99	107	98	101	96	95	93			
10.00		127	106	125	105	123	104	123	105	121	104	119	103	113	102	112	101	105	99	98	96			

