

東芝照明器具配光データシート


名 称	東芝LED照明器具
形 名	LEKD1036420L-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		800 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔		
A-A	1.3	H
B-B	1.3	H

前 面	下面開放
反射面	白色



備考	LEKD1036420L-LD9
----	------------------

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	507		
10°	508		
20°	501		
30°	470		
40°	336		
50°	115		
60°	60		
70°	39		
80°	15		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		74	68	62	59	54	53	72	67	61	58	54	52	60	57	53	52	53	52	48	47			
0.80		87	79	75	70	67	65	85	77	74	70	67	64	72	69	66	64	65	63	60	58			
1.00		93	83	81	76	74	70	90	82	80	75	73	70	78	74	71	69	70	68	65	63			
1.25		99	88	89	81	81	76	97	87	87	80	80	76	84	79	78	75	76	74	71	69			
1.50		103	91	94	85	86	80	101	90	92	84	85	80	88	83	83	79	80	78	75	73			
2.00		110	96	102	91	95	87	107	95	99	90	93	86	95	88	90	85	87	84	81	79			
2.50		114	98	106	94	100	90	110	97	104	93	98	90	99	91	94	88	91	87	84	83			
3.00		117	100	110	96	104	93	113	99	107	95	102	92	101	93	97	91	93	89	87	85			
4.00		120	102	115	99	110	97	116	101	111	98	107	96	105	96	102	94	97	93	90	89			
5.00		122	103	117	101	113	99	118	102	114	100	110	98	107	98	104	96	99	94	92	90			
10.00		126	106	124	104	121	103	122	104	119	103	117	102	112	101	110	100	104	98	97	95			

