


東芝照明器具配光データシート

名称	東芝LED照明器具
形名	CSKDD010102W05Y



効 率	F	1 %
	F	99 %
	F	100 %
	器具 光束	970 lm

保守 率	良	0.81
	中	0.77
	否	0.68

前面	下面開放
反射面	白色

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考

θ \ φ	光度 (cd/1000lm)		
	A-A	B-B	C-C
0°	379		
10°	368		
20°	350		
30°	323		
40°	272		
50°	201		
60°	130		
70°	73		
80°	33		
90°	11		
100°	5		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30		20		0
	壁	70		50		30		70		50		30		50		30		30		10		0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0
室指数	固有照明率 (×0.01)																							
0.60	64	59	51	48	42	41	63	58	50	47	42	41	48	46	41	40	40	40	35	34				
0.80	77	70	63	59	54	52	75	68	62	59	54	52	60	57	53	51	51	50	46	44				
1.00	84	75	71	65	62	58	81	74	69	65	61	58	66	63	59	57	58	56	52	50				
1.25	92	81	79	72	70	65	89	80	77	71	69	65	74	69	67	64	65	63	58	56				
1.50	96	85	85	77	76	70	93	83	82	76	74	70	79	74	72	69	70	67	63	61				
2.00	104	91	94	84	86	79	101	89	92	83	84	78	87	81	81	76	78	75	71	69				
2.50	109	94	100	88	92	83	105	92	97	87	90	82	92	85	86	81	83	79	76	74				
3.00	112	96	104	91	97	87	108	95	101	90	95	86	95	88	90	84	86	83	79	77				
4.00	117	99	110	95	104	92	112	98	106	94	101	91	100	92	96	89	91	87	84	82				
5.00	119	101	114	97	108	94	115	99	110	96	105	93	103	94	99	91	94	89	87	85				
10.00	125	104	121	102	118	101	120	103	117	101	114	100	109	99	107	97	101	95	93	91				

