

東芝照明器具配光データシート

名称	LED防爆器具
形名	LEDQ-36861SEC-LS9

--	--

効 率	F	0 %
	F	100 %
	F	100 %
	器具 光束	3600 lm

保 守 率	良	0.86
	中	0.83
	否	0.79

前面	
反射面	

最大取付間隔	
A-A	1.3 H
B-B	1.3 H

備考	
----	--

光度 (cd/1000lm)			
$\theta \setminus \phi$	A-A	B-B	C-C
0°	374		
10°	368		
20°	350		
30°	319		
40°	274		
50°	216		
60°	147		
70°	75		
80°	22		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反 射 率 (%)	天井	80						70						50						30		20		0
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0							
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0						
室指数	固有照明率 (×0.01)																							
0.60	64	59	50	48	42	41	63	58	50	47	42	40	48	46	41	40	40	39	35	34				
0.80	77	70	63	59	54	52	75	68	62	59	54	52	60	57	53	51	52	50	46	44				
1.00	84	76	71	66	62	59	82	74	69	65	61	58	67	63	60	57	58	57	52	50				
1.25	92	82	79	73	70	66	89	80	78	72	69	65	74	70	67	64	65	64	59	57				
1.50	97	85	85	77	76	71	94	84	83	76	75	70	80	74	73	69	71	68	64	62				
2.00	105	91	95	85	87	79	102	90	92	84	85	79	88	82	82	77	79	76	72	70				
2.50	110	95	101	89	93	84	106	93	98	88	91	83	93	86	87	82	84	81	77	75				
3.00	113	97	105	92	98	88	109	95	102	91	96	87	97	89	92	86	88	84	81	79				
4.00	117	100	111	96	105	93	113	98	108	95	103	92	101	93	98	90	93	89	86	84				
5.00	120	102	115	98	110	96	116	100	111	97	107	95	104	95	101	93	96	91	89	87				
10.00	125	105	123	103	120	102	121	104	118	102	116	101	111	100	99	102	97	95	93	93				

