

# ■ 東芝ランプ 配光データシート

名称	LEDユニットフラット形
形名	LDF9NHGX/C2 0/12/2
光束	1330 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F		%
	F		%
	F	100	%
	器具光束	1330	lm

最大取付間隔	
A-A	1.77 H
B-B	1.77 H

備考  
データは初期の標準値です。

光度 (cd/1000lm)			
$\theta$	$\phi$	A-A	B-B C-C
0°		156	
10°		158	
20°		163	
30°		173	
40°		185	
50°		189	
60°		183	
70°		160	
80°		108	
90°		30	
100°		10	
110°		7	
120°		7	
130°		5	
140°		2	
150°		1	
160°		0	
170°		0	
180°		0	

反射率 (%)	天井	80						70						50						30		20	0
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0						
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0	
室指数		照明率 (×0.01)																					
	0.60	53	49	37	35	27	26	51	47	36	34	27	26	34	33	26	25	25	24	19	17		
	0.80	64	58	47	44	37	35	61	56	46	43	36	35	43	41	35	34	33	33	27	24		
	1.00	71	64	55	51	44	42	68	62	53	50	43	41	50	47	41	40	39	38	33	30		
	1.25	79	71	64	58	52	49	76	68	62	57	51	48	58	54	49	47	47	45	39	36		
	1.50	85	75	70	63	59	55	81	72	67	62	57	54	63	59	54	52	52	50	44	41		
	2.00	94	82	81	72	70	64	90	79	78	70	68	63	72	67	65	61	61	59	53	50		
	2.50	100	86	88	77	78	70	95	84	84	76	75	69	78	72	71	67	67	64	59	56		
	3.00	104	89	93	81	84	75	99	87	89	80	81	74	83	76	76	71	72	69	64	61		
	4.00	109	93	100	87	93	81	105	91	97	85	90	80	89	82	84	77	79	75	71	67		
	5.00	113	96	105	90	98	86	108	93	101	89	95	84	94	85	89	81	83	79	75	72		
	10.00	121	101	116	98	112	95	115	99	111	96	108	94	103	93	100	91	93	88	85	82		

