

# 東芝ランプ 配光データシート

名称	LEDユニットフラット形 防水形
形名	LDF3L-H-GX/W4/2
光束	410 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F		%
	F		%
	F	100	%
	器具光束	410	lm

最大取付間隔	
A-A	1.18 H
B-B	1.18 H

備考  
データは初期の標準値です。

光度 (cd/1000lm)			
$\theta$	$\phi$	A-A	B-B C-C
0°		378	
10°		369	
20°		344	
30°		303	
40°		249	
50°		190	
60°		131	
70°		77	
80°		30	
90°		4	
100°		3	
110°		3	
120°		3	
130°		2	
140°		2	
150°		2	
160°		1	
170°		2	
180°		2	

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	70	50	30	50	30	50	30	30	10	0					
室指数	照明率 (×0.01)																			
0.60	62	57	49	46	41	40	60	56	48	46	40	39	47	45	40	39	38	34	32	
0.80	74	67	61	57	52	50	72	66	60	56	52	50	58	55	51	49	49	48	44	42
1.00	81	73	68	63	59	56	78	71	67	62	58	56	64	61	57	55	54	50	48	
1.25	88	78	76	70	67	63	85	77	74	69	66	62	71	67	64	61	62	60	56	54
1.50	93	82	81	74	73	68	90	80	79	73	72	67	76	71	69	66	67	65	61	59
2.00	101	87	91	81	83	76	97	86	88	80	81	75	84	78	78	73	75	72	68	66
2.50	105	90	96	85	89	80	101	89	93	84	87	79	88	81	83	78	79	76	73	71
3.00	108	93	100	88	94	84	104	91	97	87	91	83	92	84	87	81	83	79	76	74
4.00	112	96	106	92	101	88	108	94	103	91	98	87	96	88	92	85	88	84	81	79
5.00	115	97	110	94	105	91	111	96	106	93	102	90	99	90	96	88	91	86	84	81
10.00	120	101	117	99	115	97	116	99	113	98	111	96	105	95	103	94	97	92	90	88

