


東芝ランプ 配光データシート

名称	LEDユニットドーム 形 防水形
形名	LDF3N-H-GX/ WR4/2
光束	450 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F	%
	F	%
	F	100 %
	器具 光束	450 lm

最大取付間隔	
A-A	1.27 H
B-B	1.27 H

備考
データは初期の標準値です。

光度 (cd/1000lm)			
θ	A-A	B-B	C-C
0°	271		
10°	266		
20°	253		
30°	231		
40°	203		
50°	168		
60°	131		
70°	94		
80°	62		
90°	39		
100°	24		
110°	14		
120°	8		
130°	4		
140°	2		
150°	2		
160°	1		
170°	1		
180°	1		

反射率 (%)	天井	80						70						50						30		20	0
	壁	70	50	30	70	50	30	70	50	30	50	30	50	30	30	10	0						
床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0						
室指数	照明率 (×0.01)																						
0.60	56	52	42	40	34	33	54	50	41	39	33	33	39	38	32	32	31	31	26	24			
0.80	67	61	53	50	44	42	64	59	52	49	43	42	49	47	42	40	40	39	35	32			
1.00	74	66	60	56	51	48	71	64	58	54	50	47	55	52	48	46	46	44	40	37			
1.25	81	72	68	62	58	55	77	70	66	61	57	54	62	58	54	52	52	50	45	43			
1.50	86	75	73	66	64	59	82	73	71	65	62	58	66	62	59	56	56	54	50	47			
2.00	93	81	82	74	74	67	89	79	79	72	72	66	74	69	68	64	64	62	57	54			
2.50	98	85	88	78	80	72	94	82	85	76	77	71	79	73	73	68	69	66	61	58			
3.00	101	87	93	81	85	76	97	85	89	79	82	74	82	76	77	72	72	69	65	62			
4.00	106	90	99	85	92	81	101	88	95	83	89	79	87	80	83	76	77	74	70	67			
5.00	109	92	102	88	97	84	104	90	98	86	93	83	90	82	86	79	81	77	73	70			
10.00	115	96	111	94	108	91	109	94	106	92	103	90	97	88	95	86	88	83	80	77			

