

東芝ランプ 配光データシート

名称	街路灯リニューアル用 LEDランプ
形名	LDT S28L-G/2
光束	4200 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F	%
	F	%
	F	100 %
	器具光束	4200 lm

最大取付間隔	
A-A	5.08 H
B-B	5.08 H

備考	
----	--

光度 (cd/1000lm)			
θ	A-A	B-B	C-C
0°	10		
10°	16		
20°	29		
30°	44		
40°	60		
50°	76		
60°	90		
70°	101		
80°	108		
90°	110		
100°	108		
110°	101		
120°	89		
130°	74		
140°	58		
150°	41		
160°	24		
170°	8		
180°	0		

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	70	50	30	70	50	30	50	30	30	10	0				
室指数	照明率 (×0.01)																			
0.60	47	43	32	30	23	22	42	39	29	28	21	20	23	22	17	16	13	12	7	3
0.80	56	50	40	38	30	29	50	46	36	34	27	26	29	28	22	21	17	17	11	6
1.00	63	57	47	44	37	35	57	52	43	40	33	32	35	33	27	26	21	21	14	8
1.25	70	62	54	50	43	41	63	56	49	46	40	37	40	37	32	31	25	24	17	11
1.50	75	66	60	55	49	46	68	60	55	50	45	42	44	41	36	35	29	28	20	13
2.00	83	72	69	62	59	54	75	66	63	57	53	49	51	47	43	41	34	33	25	17
2.50	88	76	76	67	66	59	79	70	68	61	60	54	55	51	48	45	38	37	29	20
3.00	92	79	81	71	71	63	83	72	73	65	65	58	59	54	52	49	41	40	32	23
4.00	97	83	87	76	79	69	87	76	79	70	72	64	64	58	58	54	46	44	36	27
5.00	101	85	92	79	84	73	91	78	83	73	77	68	67	61	62	57	49	47	39	29
10.00	108	91	103	87	98	83	98	84	93	80	89	77	76	68	72	66	58	54	47	36

