

# 東芝ランプ 配光データシート

名称	街路灯リニューアル用 LEDランプ
形名	LDT58N-G-E 39/2
光束	10000 lm × 1

保守率	良	1.00
	中	1.00
	否	1.00



効率	F	%
	F	%
	F	100 %
	器具光束	10000 lm

最大取付間隔	
A-A	5.98 H
B-B	5.98 H

備考	
----	--

光度 (cd/1000lm)			
$\theta$	A-A	B-B	C-C
0°	7		
10°	14		
20°	27		
30°	43		
40°	59		
50°	75		
60°	90		
70°	101		
80°	109		
90°	111		
100°	109		
110°	101		
120°	90		
130°	75		
140°	59		
150°	43		
160°	27		
170°	14		
180°	7		

反射率 (%)	天井		80				70				50				30		20	0		
	壁	床	70	50	30	70	50	30	70	50	30	50	30	30	10	0				
室指数	照明率 (×0.01)																			
0.60	47	43	32	30	23	22	42	39	29	28	21	20	23	22	17	16	13	12	7	3
0.80	56	50	40	37	30	29	50	46	36	34	27	26	29	28	22	21	17	16	11	6
1.00	63	57	47	44	37	35	57	52	43	40	33	32	35	33	27	26	21	20	14	8
1.25	70	62	54	50	43	41	63	56	49	46	39	37	40	37	32	31	25	24	17	11
1.50	75	66	60	55	49	46	67	60	55	50	45	42	44	41	36	35	28	27	20	13
2.00	83	72	69	62	59	53	75	66	63	57	53	49	50	47	43	41	34	33	25	17
2.50	88	76	76	67	65	59	79	70	68	61	59	54	55	51	48	45	38	37	29	20
3.00	92	79	81	71	71	63	83	72	73	65	64	58	59	54	52	49	41	39	32	23
4.00	97	83	87	76	79	69	87	76	79	70	72	64	64	58	58	54	46	44	36	26
5.00	101	85	92	79	84	73	91	78	83	73	76	68	67	61	62	57	49	47	39	29
10.00	108	91	103	87	98	83	98	84	93	80	89	77	75	68	72	65	57	54	47	36

