

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEKD35341MW-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		3900 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前 面	下面開放
反射面	白色



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	720		
10°	742		
20°	737		
30°	569		
40°	208		
50°	74		
60°	22		
70°	15		
80°	8		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		83	77	73	69	67	65	82	76	72	69	67	65	71	68	66	64	65	64	61	60			
0.80		95	87	86	80	79	76	94	86	85	80	79	76	83	79	78	75	77	75	72	71			
1.00		100	90	91	84	84	80	98	89	89	84	83	80	87	82	82	79	80	78	76	75			
1.25		105	93	96	88	90	84	103	92	95	87	89	84	92	86	87	83	85	82	80	78			
1.50		109	96	100	91	94	87	106	95	98	90	93	87	95	89	90	86	88	85	83	81			
2.00		114	99	107	95	101	92	111	98	104	94	99	92	100	93	96	90	93	89	87	86			
2.50		117	101	110	98	105	95	113	100	108	97	103	94	103	95	99	93	95	92	89	88			
3.00		119	102	113	99	108	97	115	101	110	98	106	96	105	97	102	95	97	93	91	90			
4.00		122	104	117	101	113	99	118	102	114	100	110	99	108	99	105	97	100	96	94	92			
5.00		124	105	120	103	116	101	119	103	116	102	113	100	109	100	107	98	102	97	95	93			
10.00		127	106	125	105	123	105	123	105	121	104	119	104	113	102	112	106	100	98	97				

