

東芝照明器具配光データシート

名 称	東芝LED照明器具
形 名	LEKD35041MN2V-LD9

効 率	F 	0 %
	F 	100 %
	F 	100 %
器具光束		4100 lm

保守率	良	0.81
	中	0.77
	否	0.68

最大取付間隔	
A-A	1.2 H
B-B	1.2 H

前 面	下面開放
反射面	銀色梨地仕上げ



備考	
----	--

光度 (cd/1000lm)			
θ \ φ	A-A	B-B	C-C
0°	676		
10°	698		
20°	680		
30°	534		
40°	261		
50°	99		
60°	31		
70°	6		
80°	0		
90°	0		
100°	0		
110°	0		
120°	0		
130°	0		
140°	0		
150°	0		
160°	0		
170°	0		
180°	0		

反射率 (%)	天井	80						70						50						30			20	0
	壁	70		50		30		70		50		30		50		30		30			10	0		
	床	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	0		
室指数		固有照明率 (×0.01)																						
0.60		81	75	71	67	64	62	80	74	70	67	64	62	69	66	63	62	62	61	58	57			
0.80		94	85	84	79	77	74	92	84	83	78	77	74	81	77	76	73	74	73	70	69			
1.00		99	89	89	83	83	78	97	88	88	82	82	78	85	81	80	77	79	77	74	73			
1.25		104	93	95	87	89	83	102	92	94	87	88	83	91	85	86	82	84	81	79	77			
1.50		108	95	100	90	93	87	105	94	98	90	92	86	94	88	90	85	87	84	82	81			
2.00		114	99	106	95	101	92	110	98	104	94	99	91	100	93	96	90	93	89	87	85			
2.50		117	101	110	97	105	95	113	100	108	97	103	94	103	95	99	93	95	91	89	88			
3.00		119	102	113	99	108	97	115	101	110	98	106	96	105	96	102	95	97	93	91	90			
4.00		122	104	117	101	113	99	118	102	114	100	110	99	108	99	105	97	100	96	94	92			
5.00		124	104	120	103	116	101	119	103	116	102	113	100	109	100	107	98	102	97	95	94			
10.00		127	106	125	105	123	104	123	105	121	104	119	103	113	102	112	102	105	100	98	96			

